

C++ Programming on Linux

Multi-file development

CS 2308
Spring 2017

Jill Seaman

1

Programs with Multiple Files

- How the code is usually split up
 - * Put main in its own file, with helper functions
 - acts like a driver
 - * Put each class declaration in a separate *.h file (called a header file)
 - * Put the implementation of each class (the member function definitions) in its own *.cpp file
 - * Each *.cpp file (even the driver) must #include (directly or indirectly) the **header** file (*.h) of each class that it uses or implements.
 - * NEVER #include *.cpp files!!!

2

Time class, separate files

Time.h

```
#include <string>
using namespace std;

// models a 12 hour clock
class Time {
private:
    int hour;
    int minute;
    void addHour();
public:
    void setHour(int);
    void setMinute(int);
    int getHour() const;
    int getMinute() const;

    string display() const;
    void addMinute();
};
```

Driver.cpp

```
//Example using Time class
#include<iostream>
#include "Time.h"
using namespace std;

int main() {
    Time t;
    t.setHour(12);
    t.setMinute(58);
    cout << t.display() << endl;
    t.addMinute();
    cout << t.display() << endl;
    t.addMinute();
    cout << t.display() << endl;
    return 0;
}
```

3

Time class, separate files

Time.cpp

```
#include <iomanip>
#include <sstream>
#include "Time.h"
using namespace std;

void Time::setHour(int hr) {
    hour = hr;
}

void Time::setMinute(int min) {
    minute = min;
}

int Time::getHour() const {
    return hour;
}

int Time::getMinute() const {
    return minute;
}

void Time::addHour() {
    if (hour == 12)
        hour = 1;
    else
        hour++;
}

void Time::addMinute() {
    if (minute == 59) {
        minute = 0;
        addHour();
    } else
        minute++;
}

string Time::display() const {
    string hourStr = to_string(hour);
    string minuteStr = to_string(minute);
    if (minuteStr.length()==1)
        minuteStr = "0" + minuteStr;
    return hourStr + ":" + minuteStr;
}
```

4

How to compile a multiple file program

- From the command line (files in either order):

```
[... ]$g++ Time.cpp Driver.cpp
```

- * The header file should **not** be listed. (it is #included in *.cpp files)
- * one (and only one) file must have the main function
- a.out is (by default) the executable file for the entire program.

```
[... ]$ ./a.out  
12:58  
12:59  
1:00
```

5

Separate Compilation

- If we make a change to Driver.cpp, we have to recompile it
 - * but perhaps we would rather not have to recompile Time.cpp as well.
- We can compile one file at a time, and **link** the results together later to make the executable.
- Compiling without linking (use -c option):

```
[... ]$g++ -c Time.cpp  
[... ]$g++ -c Driver.cpp
```

- * -c option produces object files, with a .o extension (Time.o, Driver.o)

6

Separate Compilation

- The .o files must be **linked** together to produce the executable file (a.out):

```
[... ]$ g++ Time.o Driver.o  
[... ]$ ./a.out
```

Note there is no -c option used here

- Graphic representation:

```
g++ -c Time.cpp → Time.o  
g++ -c Driver.cpp → Driver.o  
g++ Time.o Driver.o → a.out
```

7

Separate Compilation

- Now if we change only Time.cpp, we can recompile just Time.cpp, and link the **new** Time.o file to the **original** Driver.o file:

```
[... ]$g++ -c Time.cpp  
[... ]$g++ Time.o Driver.o  
[... ]$./a.out
```

Produces new Time.o

Links new Time.o to old Driver.o, making a new a.out

8

Make

- Make is a utility that manages (separate) compilation of large groups of source files.
- After the first time a project is compiled, make re-compiles **only the changed files** (and the files depending on the changed files).
- These dependencies are defined by rules contained in a makefile.
- The rules are defined and managed by humans (programmers).

9

Make

- Rule format:

```
target: [prerequisite files]
<tab>[linux command to execute]
```

- target is a filename (or an action/goal name)
- In order to produce the target file, the prerequisite files must exist and be up to date (if not, make finds a rule to produce them).
- An example rule:

```
Time.o: Time.cpp Time.h
g++ -c Time.cpp
```

If Time.o does not exist, OR if Time.cpp or Time.h is **newer** than Time.o, (re)produce Time.o using this command

10

Makefile

- The makefile is a text file named "makefile":

```
#makefile
a.out: Driver.o Time.o
g++ Driver.o Time.o

Driver.o: Driver.cpp Time.h
g++ -c Driver.cpp

Time.o: Time.cpp Time.h
g++ -c Time.cpp
```

You can use nano to create this file

Do **not** copy/paste this to your makefile,

Don't forget the tabs

Don't call it makefile.txt

11

Make

- running make from the linux/unix prompt with no arguments executes first rule in the makefile.

- * This may trigger execution of other rules.

```
[...]$ make
```

- executing the make command followed by a target executes the rule for that target.

```
[...]$ make Time.o
```

12

Compile class + driver using make

- **Make:**

```
[... ]$ make  
g++ -c Driver.cpp  
g++ -c Time.cpp  
g++ Driver.o Time.o
```

This creates files
Driver.o, Time.o, and a.out

- **Execute:**

```
[... ]$ ./a.out  
12:58  
12:59  
1:00
```

- **Modify Driver.cpp in nano, make again:**

```
[... ]$ make  
g++ -c Driver.cpp  
g++ Driver.o Time.o
```

It knows the timestamp
of Driver.cpp is newer than
Driver.o, so it fires the
rule to make Driver.o again

- **Execute again:**

```
[... ]$ ./a.out
```